

KOLD-FLO® crack filler is applied in an easy three step process.



1

Prepare the area

Clean out debris from the cracks so the KOLD-FLO® crack filler can completely fill the damaged area.

For best results, either sweep area with UNIQUE's STIFFWITCH® broom, a street broom or blow out debris with compressed air.

Coverage per gallon

1/4" w x 1/4" d = 300 linear feet
1/2" w x 1/2" d = 75 linear feet
1" w x 1" d = 25 linear feet

2

Apply KOLD-FLO® crack filler

Using the one-gallon bottle, a pour pot or a drum pump, pour KOLD-FLO® crack filler into the crack $\frac{3}{4}$ of the length.

Allow a few minutes for **KOLD-FLO** crack filler to seep completely down into the crack. **KOLD-FLO** crack filler fills from the bottom up.



3

Complete the repair

Push KOLD-FLO® crack filler into the crack, with a "U" shaped squeegee, allowing the excess to fill the remaining $\frac{1}{4}$ of the crack.

For cracks deeper than 2" a second application of **KOLD-FLO** crack filler may be needed. Wait at least one hour prior to second application.

KOLD-FLO® is a registered trademark of UNIQUE Paving Materials Corp.



Pourable Crack Filler

QUESTIONS & ANSWERS

What type of crack filler is KOLD-FLO® crack filler?

KOLD-FLO crack filler is a specially formulated, polymer modified asphalt based emulsion designed to be used to crack fill in asphalt and concrete pavements.

Does sand need to be applied on KOLD-FLO crack filler after application?

NO! **KOLD-FLO** crack filler will surface cure between 15 and 30 minutes after application allowing for quick traffic access. Extreme cases of humidity may prolong curing up to 45 minutes. **KOLD-FLO** crack filler takes at least 8 hours to completely cure. Without proper curing, **KOLD-FLO** crack filler may become susceptible to rain washout.

Is KOLD-FLO crack filler affected by freezing temperatures?

YES! Freezing temperatures will destroy **KOLD-FLO** crack filler during storage or within 24 hours of application.



Do I need to mix or heat KOLD-FLO crack filler? **NO!** **KOLD-FLO** crack filler is ready-to-use right from the container. If settling occurs from prolonged storage, nominal agitation may be necessary.

Can you sealcoat over KOLD-FLO crack filler? **YES!** We recommend allowing **KOLD-FLO** crack filler to cure for 24 hours before sealcoating. Smaller cracks may be sealed over earlier once **KOLD-FLO** crack filler has cured.

What is the shelf life of KOLD-FLO crack filler? 6 months minimum when stored properly.

What sizes are KOLD-FLO crack filler available? **KOLD-FLO** crack filler is conveniently packaged in 8.05# 1-gallon bottles, 38# 5-gallon pails and 440# 55-gallon drums.

Distributed by:

KOLD-FLO® is a registered trademark of UNIQUE Paving Materials Corp.



Corporate Office | 800.441.4880 | 3993 E. 93rd Street, Cleveland, OH 44105 | uniquepavingmaterials.com