



L102XXX

Synthetic Rope Horizontal Lifeline System

FEATURES

- Engineered handle on the Tension-Indicating Ratchet bends when the system is properly tensioned
- In-line energy absorber is designed to limit the maximum arrest load to less than 2,500 pounds on the end anchorages
- 10,000 pound minimum breaking strength $\frac{5}{8}$ inch static kernmantle rope
- High strength polyester back pack with a reinforced bottom for easy transport
- Snap hooks are self-locking with a minimum tensile break strength of 5,000 pounds, and a 3,600 pound gate rating



SPECIFICATIONS

Model No.	Lifeline Length	Anchorage Connector	Tensioner	Max Number of Users	Capacity per User	Approx. Weight	Compliance Standards
L102030	30 ft (457 mm)	A111104 Cross Arm Strap	Tension-Indicating Ratchet	2	400 lbs (181 kg)	32 lbs (14.5 kg)	OSHA 29 CFR 1910.66 & 1926.502
L102060	60 ft (457 mm)	A111104 Cross Arm Strap	Tension-Indicating Ratchet	2	400 lbs (181 kg)	33 lbs (15.0 kg)	OSHA 29 CFR 1910.66 & 1926.502
L102100	100 ft (457 mm)	A111104 Cross Arm Strap	Tension-Indicating Ratchet	2	400 lbs (181 kg)	37 lbs (16.8 kg)	OSHA 29 CFR 1910.66 & 1926.502

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed. Users **MUST** read and understand all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to follow these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet

WERNER CO. CORPORATE HEADQUARTERS: 93 Werner Rd., Greenville, PA 16125-9499

TEL: 888-523-3370 FAX: (724) 588-0315 www.wernerco.com