



QUICK CURE

POLYURETHANE FOAM SEALANT

DAP® Touch 'n Seal® QUICK CURE Low GWP is a high performance, single component, Class 1 rated fire retardant polyurethane foam with a Global Warming Potential of less than 1. It is moisture cured, won't shrink and helps reduce energy costs.

AIR & MOISTURE BARRIER SEALANT

- Specially formulated to meet Low Global Warming Potential Requirements
- Creates a durable, air-tight seal
- Prevents air, water, and pest infiltration
- Superior adhesion to common building materials
- Reduces energy loss and helps save on heating / cooling costs
- Does not trap moisture, dust, and allergens unlike fiberglass insulation
- Closed cell structure



LOW GLOBAL WARMING POTENTIAL

DAP Touch 'n Seal utilizes innovative blowing agents and breakthrough formulas that deliver uncompromising performance and quality while greatly reducing our environmental impact. We are dedicated to providing groundbreaking and reliable products and solutions to our customers and end users, as we have since 1865.



Product #	Size	Formulation	Color	UPC	Case Qty (cu ft)	Case Volume (LxWxH)	Case Weight	Case Dimensions	Cases Per Pallet
7565000066	10 lb	High Yield / Low GWP	Light Tan	075650000663	1	0.513	16.56	7.75" x 7.75" x 14.75"	90
7565000068	16 lb	High Yield / Low GWP	Light Tan	075650000687	1	0.998	25.04	10" x 10" x 17.25"	50
7565000067	10 lb	Reduced Expansion / Low GWP	Light Tan	075650000670	1	0.513	16.56	7.75" x 7.75" x 14.75"	90
7565000069	16 lb	Reduced Expansion / Low GWP	Light Tan	075650000694	1	0.998	25.04	10" x 10" x 17.25"	50

HIGH YIELD & REDUCED EXPANSION FOAM