

ROOF & TIE-OFF

Permanent Roof Anchor

For new construction or repairs.
Stainless steel design for extended service life

12" FOR TILE ROOFS
A220300

20" FOR TILE ROOFS
A220330



Reusable Roof Anchor

Plated steel with D-Ring now approved for metal decking 24 gauge or thicker

A210400



Single Piece Roof Anchor

Stainless steel design for extended service life

A728200



Knock Down Roof Anchor

A230400/12 Pk



Cross Arm Strap

Web, Loop, D-Ring, 3" Wear Pad

2' LENGTH A111102 **4' LENGTH** A111104 **8' LENGTH** A111108

3' LENGTH A111103 **6' LENGTH** A111106 **10' LENGTH** A111110



Cross Arm Strap

Web, O-Ring, D-Ring, 3" Wear Pad

2' LENGTH A111002 **10' LENGTH** A111010 **15' LENGTH** A111020 **25' LENGTH** A111020

3' LENGTH A111003 **12' LENGTH** A111012 **20' LENGTH** A111025 **30' LENGTH** A111025

4' LENGTH A111004
6' LENGTH A111006
8' LENGTH A111008



Drop-Through Anchor

4" PLATE A710004-6 **6" PLATE** A710006-6 **12" PLATE** A710012-6



Cable Choker

5/16" vinyl coated cable, O-Rings

2' LENGTH A112002 **8' LENGTH** A112008

3' LENGTH A112003

4' LENGTH A112004

6' LENGTH A112006



Anchor Extension

1/4" vinyl coated cable, O-Ring, Snaphook

2' LENGTH A113002 **4' LENGTH** A113004

3' LENGTH A113003



ANCHOR ACCESSORIES

Twinleg Carabiner Adaptor

A100341



Carabiner

3600 lb. Gate

3/4" GATE OPENING
A100301

2" GATE OPENING
A100303



Twinleg Pin Adaptor

A100531



FALL PROTECTION

ANCHORAGE CONNECTORS

WERNER CO. CORPORATE HEADQUARTERS:

555 Pierce Road, Itasca, IL 60143

TEL: (724) 588-8600

FAX: (724) 588-0315

wernerladder.com



ACCESS A HIGHER STANDARD.™



FALL PROTECTION

GM7696 ©2020 WernerCo 2/20

FEATURED PRODUCT

Bull Ring Anchorage Connector ROOF APPLICATION

A216400

FEATURES

- Made with zinc plated steel
- Minimum Bbreaking Strength (MBS): 5,000 lb
- 2 inch connector ring
- Use on wood structures with a minimum thickness of 3 inches
- Use only with three (3) 1/4" x 3" zinc-plated steel hex head lag screws or six (6) 16D 3 inch 8 gauge spiral nails (sold separately)



SPECIFICATIONS

MODEL NO.	MATERIAL	LENGTH	WIDTH	CONNECTION SIZE	HOLE DIAMETER	MINIMUM BREAKING STRENGTH (MBS)	APPROX. WEIGHT	COMPLIANCE STANDARDS
A216400	Zinc Plated Steel	9 in (229 mm)	3 in (76 mm)	2 in (51 mm)	5/16 in (8mm) Lag 2/16 in (5mm) Nail	5,000 lbs (22.2 kN)	9.5 oz (268 g)	ANSI Z359.18-2017 Type A OSHA 1910.6 1926

D-Ring Anchorage Connector STEEL APPLICATION

A330000

FEATURES

- Made with alloy and stainless steel
- Minimum Breaking Strength (MBS): 5,000 lb
- 2-3/8 inch D-ring
- Use only on steel with a minimum thickness of 1/4 inch (6.4 mm)
- Use only with a 5/8" - 11 Grade 5 steel hex head bolt and nut (sold separately)



SPECIFICATIONS

MODEL NO.	MATERIAL	LENGTH	WIDTH	CONNECTION SIZE	HOLE DIAMETER	MINIMUM BREAKING STRENGTH (MBS)	APPROX. WEIGHT	COMPLIANCE STANDARDS
A330000	Alloy Steel Stainless Steel	6 in (154 mm)	3-1/8 in (80 mm)	2-3/8 in (61 mm)	5/8 in (17 mm)	5,000 lbs (22.2 kN)	9.5 oz (268 g)	ANSI Z359.18-2017 Type A OSHA 1910.6 1926

I-BEAM/STEEL

I-Beam Sliding Anchor

Lightweight aluminum design

FITS BEAMS 3.5" - 14" < 1.25" THICK
A550000

FITS BEAMS 12" - 30" < 2.5" THICK
A550030



Fixed Beam Anchor


FITS FLANGES 4" - 14" < 7/8" THICK
A460000



I-Beam Trolley Anchor

Lightweight aluminum design for smooth travel along beam

FITS BEAMS 3" - 10" < 7/8" THICK
A450000



Builders Grip

**FITS HOLE 3/4" - 1 1/4" DIAMETER
MAXIMUM 1 1/4" THICK MATERIAL**
A420000



Hand Grip Anchor

4" WIRE
A100204



D-Bolt Anchor

Integrated bolt with washer and nut
**1/2" STUD DIAMETER
MAXIMUM 1" THICK MATERIAL**
A320002



Mega-Swivel Steel Anchor

Swivel Top Design

DRILL HOLE 5/8" MINIMUM 1/4" THICK STEEL
A320003

REPLACEMENT STEEL BOLTS 10/PK
A320004



CONCRETE

Reusable Concrete Anchor

Easily Insert and Remove from Pre-drilled 3000 psi Concrete

DRILL HOLE 3/4" X 3" DEEP
A510000 5,000lbs

DRILL HOLE 1" X 4.5" DEEP
A510010 10,000lbs



Toggle Bolt Anchor

Reusable Anchor for Hollow Core Concrete and for Steel Beams

DRILL HOLE 3/4"
A410000



Pour-In Disposable Anchor Strap

Loop, D-Ring, Pack of 25

24" LENGTH
A211002

36" LENGTH
A211003


48" LENGTH
A211004

72" LENGTH
A211006



Parapet Wall Anchor

14.5" MAXIMUM WALL THICKNESS
A567000



Pour-In Disposable Anchor Strap

Loop, Loop, Pack of 25

36" LENGTH
A211103

48" LENGTH
A211104

72" LENGTH
A211106



Concrete Hybrid Anchor

Easily insert and remove from pre-drilled 3000 psi concrete

**REUSABLE ANCHOR
HEAVY-DUTY SWIVEL TOP
DRILL HOLE 1" X 5" DEEP**
A510002



Straight Loop Insert Anchor

Easily to use, permanent anchor system for cast in place

STRAIGHT LOOP INSERT ANCHOR/25 PK
A510021

SWIVEL STRAIGHT LOOP BOLT
A510022

STRAIGHT LOOP BOLT ASSY/25 PK
A510023



10K Mega-Swivel Concrete Anchor

Easily insert and remove from pre-drilled 3000 psi concrete, Minimum 5" concrete thickness

**HEAVY-DUTY SWIVEL TOP
DRILL HOLE 3/4" X 4.5" DEEP**
A510001

10K REPLACEMENT CONCRETE BOLTS/10 PK
A510004

