



HVAC DUCTWORK PENETRATIONS

FyreFlange® HVAC Firestop Angle & Gasket

The FyreFlange® System for HVAC ducts makes firestopping ductwork easy. The original FyreFlange® HVAC Firestop Angle consists of a powder-coated steel retaining angle with a factory-applied intumescent gasket to seal against fire and smoke while preventing deflection of the duct during fire exposure. The red color is easy to identify and inspect.

FyreFlange® Gasket is the same intumescent gasket material, but the user must provide minimum 20 GA (0.04 in or 1 mm) steel retaining angle. Convenient 150' (45.7 m) rolls allow the user to cut what is needed and minimize waste.



Features & Benefits

- Meets ASTM E814 (UL1479) and CAN/ULC-S115
- Tested for bare or insulated ducts
- No caulk or packing materials required

Gasket, 150 ft roll

Steel Angle with Gasket

Corner Clips



ORDERING INFORMATION

| Catalog Number | UPC Number | Size | (UOM) Qty. | Case Qty. | Weight (Each) |
|----------------|--------------|--|------------|-----------|--------------------|
| FFA2208 | 730573322086 | 2" x 2" x 96" (51 x 51 mm x 244 cm) (Steel Angle with Gasket) | 1 | 6/Box | 4.32 lbs (1.96 kg) |

ORDERING INFORMATION - ACCESSORIES

| Catalog Number | UPC Number | Description | (UOM) Qty. | Case Qty. | Weight (Each) |
|----------------|--------------|---|------------|-----------|--------------------|
| FFC22 | 730573300220 | 1 Bag of FyreFlange® Corner Clips (8 per bag) | 1 | 1 Bag | 0.89 lbs (0.40 kg) |
| FFG100 | 730573302217 | One (1) 150 ft roll (157 m) | 1 | 1 | 13.2 lbs (5.99 kg) |

TEST STANDARDS: ASTM E814 (UL 1479), CAN/ULC-S115
US Patent(s) US7685792B2



1-800-992-1180
stifirestop.com



[Click here to learn more about](#)



ZST13549 20220