



# SAFETY DATA SHEET

BN Products-LLC, USA

Revision date 30-Aug-2017

Version 1

## SECTION 1. IDENTIFICATION

### PRODUCT IDENTIFIER

DIAMOND BLADES (METAL BONDED AND ELECTROPLATED), DIAMOND CORE BITS, DIAMOND CUP WHEELS AND DIAMOND GRINDING DISKS

### RECOMMENDED USE

GRINDING, CUTTING AND DRILLING OF MASONRY AND CONCRETE PRODUCTS

### MANUFACTURER / DISTRIBUTOR

BN PRODUCTS-USA, LLC  
3450 SABIN BROWN RD.  
WICKENBURG, AZ 85390  
P: 800-992-3833  
F: 928-684-7041

### EMERGENCY PHONE NUMBER

FOR CHEMICAL EMERGENCY SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL 928-232-2449

## SECTION 2. HAZARDS IDENTIFICATION

### PRECAUTIONARY STATEMENTS

AVOID INHALATION OF DUSTS AS WELL AS PROLONGED AND REPEATED CONTACT WITH SKIN. MOST DIAMOND TOOLS ARE USED ALONG WITH WATER TO KEEP BLADES COOL AND TO DECREASE AIRBORNE CONTAMINANTS. FOR DRY SAWING AND GRINDING, MAINTAIN ADEQUATE VENTILATION OR USE LOCAL EXHAUST.

### DESCRIPTION OF HAZARDS

DUST CREATED BY GRINDING AND/OR SAWING CAN CAUSE IRRITATION TO EYES, NOSE, THROAT AND SKIN. LONG TERM OVEREXPOSURE TO DUSTS CAN LEAD TO RESPIRATORY IMPAIRMENT. GRINDING OR SAWING MAY PRODUCE AN ELEVATED NOISE WHICH CAN AFFECT HEARING. PARTICLES OF VARIOUS SIZE EJECTED DURING GRINDING OR SAWING MAY POSE IMPACT HAZARDS TO EYES AND SKIN.

## SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE DESCRIPTION	CAS#
DIAMOND	7782-40-3
NICKEL	7440-02-0
COBALT	7440-48-4
IRON	7439-89-6
COPPER	7440-50-8
TIN	7440-31-5
TUNGSTEN CARBIDE	12070-12-1
MANGANESE	7439-96-5

**SECTION 4. FIRST AID MEASURES****INHALATION**

IF SYMPTOMS DEVELOP (COUGHING, WHEEZING, SHORTNESS OF BREATH, ETC), REMOVE FROM EXPOSURE AND OBTAIN MEDICAL ASSISTANCE, AS NEEDED.

**SKIN CONTACT**

IF IRRITATION OCCURS, WASH AFFECTED AREAS WITH SOAP AND WATER. OBTAIN MEDICAL ASSISTANCE, AS NEEDED.

**EYE CONTACT**

IF IRRITATION OCCURS, FLUSH WITH LARGE AMOUNTS OF WATER. OBTAIN FIRST AID AND MEDICAL ASSISTANCE, AS NEEDED.

**INGESTION**

OBTAIN MEDICAL ASSISTANCE.

**SECTION 5. FIRE FIGHTING MEASURES**

SUITABLE (AND UNSUITABLE) EXTINGUISHING MEDIA: N/A

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL: N/A

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: N/A

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

PERSONAL PRECAUTION, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: N/A

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: CLEAN-UP: N/A

**SECTION 7. HANDLING AND STORAGE****PRECAUTIONS FOR SAFE HANDLING**

MAINTAIN GOOD HOUSEKEEPING PRACTICES TO PREVENT ACCUMULATION OF DUST.

**CONDITIONS FOR SAFE STORAGE**

STORE BLADES, BITS, WHEELS AND DISK IN A DRY LOCATION.

**SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

CHEMICAL NAME	OSHA PEL	ACGIH TLV (mg/m <sup>3</sup> )
DIAMOND	N/A	N/A
NICKEL	1.0 mg/m <sup>3</sup>	1.5 mg/m <sup>3</sup>
COBALT	0.1 mg/m <sup>3</sup>	0.02 mg/m <sup>3</sup>
IRON	N/A	N/A
COPPER	0.1 mg/m <sup>3</sup>	0.2 mg/m <sup>3</sup>
TIN	2.0 mg/m <sup>3</sup>	2.0 mg/m <sup>3</sup>
TUNGSTEN CARBIDE	5.0 mg/m <sup>3</sup>	5.0 mg/m <sup>3</sup>
MANGANESE	5.0 mg/m <sup>3</sup>	0.2 mg/m <sup>3</sup>

**APPROPRIATE ENGINEERING CONTROLS**

AVOID INHALATION OF DUSTS AS WELL AS PROLONGED AND REPEATED CONTACT WITH SKIN. DURING SAWING OR GRINDING, MAINTAIN ADEQUATE VENTILATION OR USE LOCAL EXHAUST FOR DUST CONTROL. HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

**PERSONAL PROTECTIVE EQUIPMENT****RESPIRATORY PROTECTION**

WEAR OSHA APPROVED RESPIRATOR IF AIRBOURNE DUST CONCENTRATIONS EXCEED PEL OR TLV LEVELS.

**SKIN PROTECTION**

NOT NORMALLY REQUIRED. PROTECTIVE CLOTHING AND GLOVES MAY BE WORN TO LIMIT CONTACT.

**EYE PROTECTION**

USE OSHA APPROVED FACE SHIELD OR SAFETY GLASSES.

**HEARING PROTECTION**

WEAR APPROVED HEARING PROTECTOR WHERE NOISE LEVELS DURING SAWING AND GRINDING EXCEED OSHA PRESCRIBED LEVELS.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>APPEARANCE:</b> SOLID	<b>ODOR:</b> ODORLESS ODOR	<b>THRESHOLD:</b> N/A
<b>PH:</b> N/A	<b>MELTING POINT:</b> 1166-2192F	<b>BOILING POINT:</b> N/A
<b>FLASH POINT:</b> N/A	<b>EVAPORATION RATE:</b> N/A	<b>FLAMMABILITY:</b> N/A
<b>UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:</b> N/A		<b>VAPOR PRESSURE:</b> N/A
<b>VAPOR DENSITY:</b> N/A	<b>SPECIFIC GRAVITY:</b> 7.8 - 12.4	
<b>SOLUBILITY IN WATER:</b> INSOLUBLE		
<b>PARTITION COEFFICIENT:</b> N/A	<b>AUTO-IGNITION TEMP:</b> N/A	<b>DECOMPOSITION TEMP:</b> N/A
<b>VISCOSITY:</b> N/A		

**SECTION 10. STABILITY AND REACTIVITY**

**REACTIVITY:** NO DATA AVAILABLE

**CHEMICAL STABILITY:** STABLE UNDER NORMAL USE AND STORAGE CONDITIONS.

**PASSIBILITY OF HAZARDOUS REACTIONS:** NO DATA AVAILABLE

**CONDITIONS TO AVOID:** KEEP AWAY FROM HUMIDITY AND EXCESSIVE HEAT

**INCOMPATIBLE MATERIALS:** STRONG ACIDS AND OXIDIZING AGENTS

**HAZARDOUS DECOMPOSITION PRODUCTS:** NONE

**SECTION 11. TOXICOLOGICAL INFORMATION****COMPONENT INFORMATION**

<b>CHEMICAL NAME</b>	<b>LD50 TOXICITY</b>	<b>CARCINOGEN*</b>
DIAMOND	MOUSE – 10,000 mg/kg	N
NICKEL	NO DATA AVAILABLE	Y
COBALT	RAT – 6,171 mg/kg	N
IRON	RAT – 7,500 mg/kg	N
COPPER	MOUSE – 3.5 mg/kg	N
TIN	RAT - >2,000 mg/kg	N
TUNGSTEN	CARBIDE RAT – 2,000 mg/kg	N
MANGANESE	RAT – 9,000 mg/kg	N

\*PER NATIONAL TOXICOLOGY PROGRAM 13TH REPORT ON CARCINOGENS, OCT 2, 2014.

## **ROUTES OF ENTRY**

ROUTE OF ENTRY, INHALATION: YES

ROUTE OF ENTRY, SKIN: NO

ROUTE OF ENTRY, INGESTION: NO

## **SYMPTOMS OF EXPOSURE**

ACUTE: IRRITATION, COUGHING, WHEEZING, SHORTNESS OF BREATH

DELAYED / CHRONIC: RESPIRATORY CONDITIONS

## **SECTION 12. ECOLOGICAL INFORMATION**

PRODUCTS HAVE NO ECOLOGICAL EFFECTS WHEN PROPERLY USED AND STORED. AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL HANDLING OR DIAPOSAL. NO DATA AVAILABLE.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

### **WASTE DISPOSAL**

USE STANDARD LANDFILL METHODS CONSISTENT WITH APPLICABLE FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS.

## **SECTION 14. TRANSPORT INFORMATION**

NO SPECIFIC REGULATIONS FOR TRANSPORTATION ARE REQUIRED. MAKE SURE TO PROTECT PRODUCTS FROM DAMAGE DURING TRANSPORTATION.

## **SECTION 15. REGULATORY INFORMATION**

### **CALIFORNIA PROP. 65 COMPONENTS**

WARNING! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. COBALT CAS-NO. 7440-48-4, NICKEL CAS-NO. 7440-02-0, REVISION DATE 2007-09-28

## **SECTION 16. OTHER INFORMATION**

**SDS REVISION DATE:** AUGUST 1, 2017

**REASON FOR UPDATE:** INITIAL CREATION

### **DISCLAIMER**

THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE TAKEN FROM SOURCES BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF; HOWEVER, THE COMPANY MAKES NO WARRANTY WITH RESPECT TO THE ACCURACY OF THE INFORMATION OR THE SUITABILITY OF THE RECOMMENDATIONS, AND ASSUMES NO LIABILITY TO ANY USER THEREOF.