



GRADE: Gun Foam 

COLOR: Bright White Foam 

NO-WARP

WINDOW & DOOR FOAM SEALANT

Touch 'n Seal® No-Warp Foam Sealant is formulated to permanently seal around doors, windows and skylights without bowing jams or deflecting frames.

LOW PRESSURE FORMULA MEETS AAMA 812-04

- Low expansion and pressure during cure for sealing windows & doors
- Meets AAMA 812-04
- ICC-ES ESR-1926 approved
- Bright white color
- Application temperature range 50°F to 100°F (10°C to 38°C)
- Class A Fire Rated
- Interior and exterior use

IDEAL FOR

- Cracks & Gaps up to 1 1/2" (38 mm)
- Insulate, Block Drafts & Moisture
- Window & Door Safe

TECH DATA

Density:	1.3 - 1.8 pcf
R-Value:	4.5/in (25mm)
Tack-Free:	10 minutes
Cuttable:	30 minutes
Cure:	1 hour
ASTM E84:	Flame Spread 10 Smoke Developed 15
Yield (1/4" bead):	2,100 linear ft
Shelf Life:	18 months



Product #	Size	Color	UPC	GTIN 14	Case Pk	Case Weight (lb)	Case Vol. (cu ft)	Case Dimensions (LxWxH)	Case Per Pallet
7565029712	20 oz	Bright White	0 75650 29712 4	100 75650 29712 1	12	20.39	0.749	11"x 8.75"x 11.5"	72

WINDOW & DOOR FOAM SEALANT

31041_2201