



C311104

DeCoil 3 Foot Energy Absorbing Lanyard

FEATURES

- DeCoil 3 foot (0.9m) Energy Absorbing Lanyard
- 1 inch polyester webbing with WebAlert™
- Rated for a 6 foot free fall for users up to 310 pounds (141 kg)
- Steel snap hooks are self-locking with a minimum tensile break strength of 5,000 pounds and a 3,600 pound gate rating



WebAlert™
INSPECTABLE WEBBING



SPECIFICATIONS

Model No.	Harness Connector	Anchorage Connector	Lifeline	Length	Approx. Weight
C311104	Steel Snap Hook	Steel Snap Hook	1 in Polyester Web	3 ft (0.9 m)	2.6 lbs (1.18 kg)

COMPLIANCE STANDARDS

Meets	Maximum Arrest Distance	Average Arrest Force	Maximum Arrest Force	Free Fall Limit	Capacity
ANSI Z359.13-2013	48 in (1.2 m)	900 lbf (4 kN)	1,800 lbf (8 kN)	6 ft (1.8 m)	130 - 310 lbs (59 - 141 kg)
OSHA 29 CFR 1910.140 / 1926.502	42 in (1,067 mm)	N/A	1,800 lbf (8 kN)	6 ft (1.8 m)	130 - 310 lbs (59 - 141 kg)

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed. Users MUST read and understand all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to follow these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet