



HEAD-OF-WALL • WALL-TO-WALL • BOTTOM-OF-WALL

SpeedFlex® Track Top Gasket

SpeedFlex® TTG Track Top Gasket makes short work of construction joints in gypsum board construction. TTG eliminates the need for firestop sealants or sprays by firestopping as the wall is constructed. Track Top Gasket is easily cut to length with scissors or a sharp knife, installing quick with no waste.

Features & Benefits

- Works with any ceiling track
- Tested for both standard and shaft wall construction
- Allows for 100% compression and extension
- Red in color for easy identification and inspection
- Tested in Head-of-Wall, Wall-to-Wall, and Bottom-of-Wall Joints



ORDERING INFORMATION

Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)
TTG250J	730573082508	Track Top Gasket for 2.5" (63.5 mm) J-Runners - 150' (45.7 meter) roll	1	1	16.57 lbs (7.52 kg)
TTG350F	730573083550	Track Top Gasket with folded legs for 3-1/2" (89 mm) or 3-5/8" (92 mm) ceiling track - 2' x 80.5' (24.5 meter) rolls	1	1	16.58 lbs (7.52 kg)
TTG400J	730573084007	Track Top Gasket for 4" (102 mm) J-Runners - 150' (45.7 meter) roll	1	1	18.62 lbs (8.45 kg)
TTG600F	730573086049	Track Top Gasket with folded legs for 6" (152 mm) ceiling track - 2' x 80.5' (24.5 meter) rolls	1	1	23.47 lbs (10.65 kg)
TTG600J	730573086025	Track Top Gasket for 6" (152 mm) J-Runners - 150' (45.7 meter) roll	1	1	23.64 lbs (10.72 kg)

TEST STANDARDS: ASTM E1966, UL 2079, CAN/ULC-S115



1-800-992-1180
stifirestop.com



Click here to learn more about

