ARMOR GUYS
· PROTECTED ·

HAMMER HEAD 3™
BASETEK



ANSI A3 CUT
EN388
4442C
CE
CONFIDENCE IN TEXTILES
Tested for harmful substances according to Oeko-Tex® Standard 100
SHCO 098266 TESTEX

02-023 SPECIFICATION SHEET

ATTRIBUTES:

LINER
13g Salt and Pepper HDPE
A3 Basetek Liner

COATING
Black HCT® MicroFoam
Nitrile Palm Coating

FEATURES:

- Enhanced Grip in Oily and Greasy Environments

APPLICATIONS:

- Automotive Manufacturing
- Light Manufacturing
- Sheet Metal Handling
- Metal Stamping
- Construction

Armor Guys reference number : 02-023

CATEGORY:

Basetek

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:

BASETEK Innovative Fiber Technology
HCT Hybrid Coating Technology

SPECIFICATIONS

LINER MATERIALS	13g Salt and Pepper HDPE A3 Basetek Liner
COATING MATERIALS	Black HCT® MicroFoam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	XS-XXL

PACKAGING						
CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ
CASE WEIGHT	24.03/lbs	24.69/lbs	26.23/lbs	27.77/lbs	30.97/lbs	33.28/lbs
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4442C	EN Level 4 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F